

LUKOIL GENESIS SPECIAL C3 5W-40

Product number: 563105

Synthetic engine oil for gasoline and diesel engines with DPF

APPROVALS

API SN
BMW LL-04
Ford WSS-M2C917-A
GM dexos2™-licensed GB2C0426072
MB-approval 229.51
Porsche A40
Renault RN 0700/ 0710
VW 502 00/ 505 00/ 505 01

MEETS REQUIREMENTS

ACEA C3
API CF
Fiat 9.55535 S2
MB 229.31, 226.5

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL C3 5W-40 is a synthetic engine oil for up-to-date gasoline and diesel engines with particulate filter. It offers high reliability and allows maximum reduction of fuel consumption. The Mid SAPS-Level protects the environment as well as the particulate filter because of the low content of sulphated ash, phosphor and sulphur.

LUKOIL GENESIS SPECIAL C3 5W-40 minimized oil related emissions and guarantees maximum protection of the environment.

LUKOIL GENESIS SPECIAL C3 5W-40 reduced ash formula provide long durability of particulate filter.

LUKOIL GENESIS SPECIAL C3 5W-40 latest additive technology keeps the engine clean, reduces friction and guarantees maximum engine lifetime.

LUKOIL GENESIS SPECIAL C3 5W-40 provide long oil drain intervals and thereby high economy.

APPLICATION

LUKOIL GENESIS SPECIAL C3 5W-40 can be used in many newer passenger cars, gasoline and diesel engines with DPF, especially for BMW, Mercedes Benz, Opel and Volkswagen.

LUKOIL GENESIS SPECIAL C3 5W-40 is recommended to use in LPG (Liquefied Petroleum Gas) engines requiring Mid SAPS engine oils.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL C3 5W-40
Density @ 15°C	kg/m ³	DIN 51575	849
Flash point COC	°C	ISO 2592	220
Viscosity class	---	SAE J 300	5W-40
Viscosity @ 40°C	mm ² /s	DIN 51562/T1	76,7
Viscosity @ 100°C	mm ² /s	DIN 51562/T1	13,2
Viscosity index	---	DIN ISO 2909	175
Pour point	°C	DIN ISO 3016	<-39

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH

21 May 2019, Page 1/1

* This document supersedes all previous versions

 Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe GmbH
 Uferstrasse 8
 1220 Vienna, Austria

+43(1)205 222-8800
www.lukoil-lubricants.eu

member of:

