

# LUKOIL LAYER CLASSIC

high-grade forming- and molding-oil for concrete-formworks made from steel and timber

## APPROVALS

## MEETS REQUIREMENTS

### PRODUCT DESCRIPTION

**LUKOIL LAYER CLASSIC** is a non-emulsifiable molding-lubricant that provides easy and perfect separation of formworks and concrete. Use of **LUKOIL LAYER CLASSIC** results in perfect concrete-surface and clean formworks. Moreover, harmful residues of oil in concrete can be avoided.

Steel formworks are perfectly protected against rust, timber is protected against rotteness. Due to a stable oil-film best efficiency is guaranteed.

### APPLICATION

For a successful and economical use **LUKOIL LAYER CLASSIC** should best be applied evenly and very thin with a brush, roller or a spray lance.

#### **consumption:**

untreated wooden formwork 1 liter for 20 m<sup>2</sup>  
 Plastic & metal molds 1 liter for 50 m<sup>2</sup>

The consumption data should not be exceeded in order to achieve a high quality of the concrete surface.

### TYPICAL TEST DATA

| PROPERTY           | Units              | Test methods | LUKOIL LAYER CLASSIC |
|--------------------|--------------------|--------------|----------------------|
| Density at 15°C    | kg/m <sup>3</sup>  | DIN 51757    | 860                  |
| Flash point COC    | °C                 | ISO 2592     | >150                 |
| Viscosity at 40°C  | mm <sup>2</sup> /s | DIN 51562/T1 | 11                   |
| Viscosity at 100°C | Mm <sup>2</sup> /s | DIN 51562/T1 | -                    |
| Pour point         | °C                 | DIN ISO 3016 | <-21                 |

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

26 September 2017, Page 1/1

\* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants [technics.lubes@lukoil.com](mailto:technics.lubes@lukoil.com)

LUKOIL Lubricants Europe GmbH  
 Uferstrasse 8  
 1220 Vienna, Austria

+43(1)205 222-8800  
[www.lukoil-lubricants.eu](http://www.lukoil-lubricants.eu)

member of:

